



TELESWIVEL

2" BALL PINTLE

TeleSwivel 2" Ball Pintle Instruction Sheet

Disclaimer: The ratings of the TeleSwivel System represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

The TeleSwivel System consists of two separate parts: the 210 Accessory Channel Hitch (not included) and an accessory of your choice. These instructions apply to the 2" Ball Pintle accessory only, as pictured.



The towing capacities of the TeleSwivel 210 Accessory Channel are **5,000 lbs. gross trailer weight and 500 lbs. tongue weight** when towing with the 2" Ball pintle.

1. Install 210 Accessory Channel Hitch (not included) into the 2" receiver hitch of your vehicle and secure with a hitch pin and clip as per instructions included with that unit.
2. Install the Ball Pintle into the Accessory Channel using only the pins and clips provided in the 210 Accessory Channel Hitch. **See illustration below .**

Note: The pins included with your TeleSwivel 210 Accessory Channel Hitch platform are specifically engineered for the TeleSwivel System. If replacement pins are needed, they must be replaced with original factory TeleSwivel pins. **Use of any pin other than of TeleSwivel manufacture could be a serious safety hazard and will void the warranty.**

3. Prior to towing, check to make sure that the pins are secured into place with cotter pins.
4. Never hook up trailer safety chains to the TeleSwivel System.

Warning: Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever **is less**. See your Vehicle Owners Manual to determine Vehicle Tow Rating.

Warning: Please insure that the safety chains operate freely around the TeleSwivel system and do not become entangled in the Accessory Channel Hitch or Ball Pintle accessory.

Warning: Maintain adequate vertical (tongue) load to properly control the trailer (generally 10%), but do not exceed the above rated capacities.

Warning: Before installation or use, be sure to check that the nut of the pintle ball is torque set to 260 ft/lbs or more.



Ball Pintle Installed in 210 Accessory Channel Hitch



TELESWIVEL

DUAL BALL

US Patent #8,033,563

TeleSwivel Dual Ball Instruction Sheet

Disclaimer: The ratings of the TeleSwivel System represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

The TeleSwivel System consists of two separate parts: the 210 Accessory Channel Hitch (not included) and an accessory of your choice. These instructions apply to the Dual Ball accessory only, as pictured.



The towing capacities of the TeleSwivel 210 Accessory Channel are **7,000 lbs. gross trailer weight and 700 lbs. tongue weight** when towing with the 2 5/16" ball, and **5,000 lbs. gross trailer weight and 500 lbs. tongue weight** when towing with the 2" ball.

1. Install a 210 Accessory Channel Hitch (not included) into the 2" receiver hitch of your vehicle and secure with a hitch pin and clip as per instructions included with that unit.
2. Install the Dual Ball into the Accessory Channel using only the pins and clips provided in the 210 Accessory Channel Hitch. **See illustration below .**

Note: The pins included with your TeleSwivel 210 Accessory Channel Hitch platform are specifically engineered for the TeleSwivel System. If replacement pins are needed, they must be replaced with original factory TeleSwivel pins. **Use of any pin other than of TeleSwivel manufacture could be a serious safety hazard and will void the warranty.**

3. Prior to towing, check to make sure that the pins are secured into place with cotter pins.
4. Never hook up trailer safety chains to the TeleSwivel System.

Warning: Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less. See your Vehicle Owners Manual to determine Vehicle Tow Rating.

Warning: Please insure that the safety chains operate freely around the TeleSwivel system and do not become entangled in the Accessory Channel Hitch or Dual Ball accessory.

Warning: Maintain adequate vertical (tongue) load to properly control the trailer (generally 10%), but do not exceed the above rated capacities.



Dual Ball Installed in 210 Accessory Channel Hitch